NSN 5905-00-192-2731

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-192-2731 **Section Quantity:** 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.210 inches **Shaft Diameter:** 0.100 inches **Shaft Length:** 0.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.750 inches **Body Width:** 0.160 inches **Body Height:** 0.310 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Center To Center Distance Between Terminals:** 0.500 inches **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Cubic Measure:** 0.037 cubic inches **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 7200.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.200 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0 to 250.0 single section

NSN 5905-00-192-2731

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: