

View Online at <https://aerobasegroup.com/nsn/5905-00-192-2958>

**Section Quantity:**

2

**Reliability Indicator:**

Not established

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.250 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

800.000 percent, rated amperes c and better industrial clears

**Unable To Decode:**

Unable to decode and 40.0 ohms at 4 pct rotation second section and 3000.0 ohms at 10 pct rotation second section and unable to decode and unable to decode

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 all sections

**Special Features:**

W/insulated contact arm, metallic shaft matl, fully enclosed resistive incl method, reliability indicator not established

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0