

View Online at <https://aerobasegroup.com/nsn/5905-00-192-2958>

Section Quantity:

2

Reliability Indicator:

Not established

Shaft Diameter:

0.250 inches

Shaft Length:

1.250 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

800.000 percent, rated amperes c and better industrial clears

Unable To Decode:

Unable to decode and 40.0 ohms at 4 pct rotation second section and 3000.0 ohms at 10 pct rotation second section and unable to decode and unable to decode

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Special Features:

W/insulated contact arm, metallic shaft matl, fully enclosed resistive incl method, reliability indicator not established

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0