Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-192-2979

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

# **Body Diameter:**

1.062 inches

### Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.375 inches

Body Length:

# 0.562 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Fragility Factor:

Moderately rugged

## Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

### Terminal Location:

Radially positioned over less than half the circumference

### **Mounting Method:**

Locking bushing

#### **Features Provided:**

Nonmetallic shaft and shaft locking device

### **Electrical Resistance Per Section:**

6.0 ohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Standard Taper Curve Per Section:

A single section



# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0