NSN 5905-00-192-3933

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-192-3933

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 100.0/+100.0 Electrical Resistance: 88.100 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.0001 Ferminal Length: 1.500 inches 80dy Diameter: 2.188 inches 80dy Length: 1.625 inches
Electrical Resistance: 58:100 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 1.625 inches
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches 30dy Diameter: 0.188 inches 30dy Length: 1.625 inches
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches 30dy Diameter: 0.188 inches 30dy Length: 1.625 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Rody Diameter: 0.188 inches Rody Length: 1.625 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 1.625 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Terminal Length: 1.500 inches Body Diameter: 1.188 inches Body Length: 1.505 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Ferminal Length: 1.500 inches Body Diameter: 1.188 inches Body Length: 1.505 inches
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
Reliability Failure Rate Level In Percent: 0.001 Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
Reliability Failure Rate Level In Percent: 0.001 Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
0.001 Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
Ferminal Length: 1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
1.500 inches Body Diameter: 0.188 inches Body Length: 0.625 inches
Body Diameter: 0.188 inches Body Length: 0.625 inches
0.188 inches Body Length: 0.625 inches
Body Length: 0.625 inches
0.625 inches
Power Dissipation Rating In Watts:
0.250 free air
Style Designator:
Axial terminal each end
Fest Data Document:
81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg: