NSN 5905-00-192-7232

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-192-7232 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 0.391 inches **Body Diameter:** 0.750 inches **Mounting Stud Length:** 0.093 inches **Mounting Bushing Length:** 0.188 inches **Body Length:** 0.188 inches **Actuator Type:** Integral knob **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Fragility Factor:** Moderately delicate **Screw Thread Diameter:** 0.073 inches **Screw Thread Series Designator:** Unf Screw Thready Qty Per Inch (tpi): 72.0 **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Threaded stud **Electrical Resistance Per Section:** 1.5 megohms single section **Rotary Actuator Travel In Angular Deg:** 260.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 70.0 single section

Power Dissipation Rating Per Section In Watts:

0.1 free air single section

NSN 5905-00-192-7232

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
C single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No