NSN 5905-00-192-9123

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-192-9123

Section Quantity:
1
Body Style:
Rectangular w/bushing
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.719 inches
Body Width:
0.938 inches
Body Height:
1.125 inches
Shaft Style:
Round
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.438 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):

32.0

NSN 5905-00-192-9123

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
10.000 megohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Switch Current Type And Rating In Amps:
3.000 ac/dc
Standard Taper Curve Per Section:
N single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0