Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-192-9141

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

1.062 inches

### Shaft Diameter:

0.250 inches

### Shaft Length:

0.688 inches

### Mounting Bushing Length:

0.375 inches

### Body Length:

# 0.562 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Locking bushing

#### **Electrical Resistance Per Section:**

25.0 kilohms single section

## Power Dissipation Rating Per Section In Watts:

0.25 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

## Standard Taper Curve Per Section:

A single section

#### **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0