## NSN 5905-00-192-9162

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-192-9162

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Cylindrical bushing mounted                               |
| Reliability Indicator:                                    |
| Not established   |
| Overall Length:   |
| 1.437 inches  |
| Body Diameter:  |
| 1.062 inches  |
| Shaft Diameter:   |
| 0.250 inches  |
| Shaft Length:   |
| 0.875 inches  |
| Mounting Bushing Length:                                  |
| 0.375 inches  |
| Body Length:  |
| 0.562 inches  |
| Shaft Style:  |
| Round   |
| Shaft Bearing Type:                                       |
| Bearing   |
| Actuator Type:  |
| Single shaft  |
| Nonturn Device Location:                                  |
| At 9 oclock   |
| Nonturn Device Radius:                                    |
| 0.531 inches  |
| Screw Thread Diameter:                                    |
| 0.375 inches  |
| Screw Thread Series Designator:                           |
| Unef  |
| Screw Thready Qty Per Inch (tpi):                         |
| 32.0  |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Standard bushing  |
| Electrical Resistance Per Section:                        |
|   |
| 3.000 kilohms single section                              |
| Power Dissipation Rating Per Section In Watts:            |

2.0 free air single section

## NSN 5905-00-192-9162

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Resistance Tolerance Per Section In Percent: |
|--|
| -10.0 to 10.0 single section                 |
| Standard Taper Curve Per Section:            |
| A single section                             |
| Terminal Type And Quantity:                  |
| 3 tab, solder lug                            |
| Shelf Life:                                  |

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0