NSN 5905-00-192-9883

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-192-9883

Section Quantity:		
1		
Body Style:		
Cylindrical bushing mounted		
Reliability Indicator:		
Not established		
Body Diameter:		
1.680 inches		
Shaft Diameter:		
0.250 inches		
Shaft Length:		
0.875 inches		
Mounting Bushing Length:		
0.500 inches		
Body Length:		
1.410 inches		
Shaft Style:		
Round		
Contact Arm Electrical Off Position:		
Fully ccw		
Actuator Type:		
Single shaft		
Fragility Factor:		
Rugged		
Screw Thread Diameter:		
0.500 inches		
Screw Thread Series Designator:		
Un		
Screw Thready Qty Per Inch (tpi):		
32.0		
Terminal Location:		
Radially positioned over less than half the circumference		
Mounting Method:		
Standard bushing		
Electrical Resistance Per Section:		
190.0 ohms single section		
Power Dissipation Rating Per Section In Watts:		
100.0 free air single section		
Resistance Tolerance Per Section In Percent:		
-10.0 to 10.0 single section		

A single section

Standard Taper Curve Per Section:

NSN 5905-00-192-9883

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Special	reatui	es
Fourth to	arminal	at

Fourth terminal at low resistance end

Terminal Type And Quantity:

4 tab, solder lug

.,

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0