NSN 5905-00-193-2138

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-193-2138

Section Quantity: 1 Body Style: Cylindrical bushing mounted Reliability Indicator: Not established First Flat Length:
Body Style: Cylindrical bushing mounted Reliability Indicator: Not established
Cylindrical bushing mounted Reliability Indicator: Not established
Reliability Indicator: Not established
Not established
First Flat Length:
instructiong.ii.
1.562 inches
Flat Height:
0.344 inches
Body Diameter:
6.000 inches
Shaft Diameter:
0.375 inches
Shaft Length:
2.000 inches
Mounting Bushing Length:
0.375 inches
Body Length:
2.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
20.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.200 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
300.0 free air single section
Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

NSN 5905-00-193-2138

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No **Fiig:**

- -- 9-

A002a0