

View Online at <https://aerobasegroup.com/nsn/5905-00-193-4465>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Terminal Length:

0.500 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.070 inches

Body Length:

1.250 inches

Body Width:

0.328 inches

Body Height:

0.437 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully ccw-cw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3960.0

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Center To Center Distance Between Terminals:

0.700 inches

Fragility Factor:

Moderately delicate

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal and unthreaded hole

Center To Center Distance Between Terminal Rows:

0.100 inches

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

4140.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0