Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-193-6846

Section	Quantity:

1

- Body Style: Rectangular w/mounting holes
- Reliability Indicator:
- Not established
- Terminal Length:
- 0.500 inches
- Mounting Hole Diameter:
- 0.078 inches
- Shaft Diameter:
- 0.080 inches
- Shaft Length:
- 0.035 inches
- Body Length:
- 0.500 inches
- **Body Width:**
- 0.220 inches
- Body Height:
- 0.500 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- Effective Electrical Rotation In Deg Angular Rotation:
- 7920.0
- Center To Center Distance Between Terminals:
- 0.200 inches
- Lateral Distance Between Mounting Hole Centers:
- 0.520 inches
- Mounting Facility Quantity:
- 2
- Terminal Location:
- Rear end
- **Mounting Method:**
- Unthreaded hole
- **Electrical Resistance Per Section:**
- 20.000 kilohms single section
- **Rotary Actuator Travel In Angular Deg:**
- 7920.0
- Center To Center Distance Between Center Terminal And Outside Terminal:
- 0.100 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0