## NSN 5905-00-193-7320

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-193-7320 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.469 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Grounded contact arm

**Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** 

-15.0 to 15.0 single section

2.0 kilohms single section

**Standard Taper Curve Per Section:** 

**Electrical Resistance Per Section:** 

A single section

## NSN 5905-00-193-7320

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 3 tab, solder lug           |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |

Demilitarization:

No **Fiig:** 

A002a0