Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-195-2317

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

1.508 inches

#### Body Diameter:

2.410 inches

### Shaft Diameter:

0.125 inches

#### Shaft Length:

Between 0.829 inches and 0.922 inches

#### Mounting Bushing Length:

Between 0.328 inches and 0.442 inches

#### **Body Length:**

1.440 inches

#### Shaft Style:

Round, slotted

## Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

#### Maximum Starting Torque:

40.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

#### Nonturn Device Location:

At 12 oclock

#### Nonturn Device Radius:

Between 0.485 inches and 0.515 inches

#### Fragility Factor:

Moderately rugged

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference



**Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 350.0 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 295.0 and 310.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section **Power Dissipation Rating Per Section In Watts:** 50.0 heat sink single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug **Specification Data:** 81349-mil-r-22/5 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0

---