NSN 5905-00-195-4498

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-195-4498

Section Quantity:
1
Reliability Indicator:
Not established
First Flat Length:
2.000 inches
Flat Height:
0.216 inches
Shaft Diameter:
0.250 inches
Shaft Length:
2.500 inches
Mounting Bushing Length:
0.375 inches
Overall Diameter:
1.281 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.000 kilohms single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

N/a

NSN 5905-00-195-4498

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0