NSN 5905-00-195-8377

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-195-8377 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.500 inches **Body Diameter:** 1.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.375 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.875 inches **Overall Diameter:** 1.313 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.469 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:**

3.0 kilohms 2nd section

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

NSN 5905-00-195-8377

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section in Percei
-20.0 to 20.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0