Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-195-9451

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.858 inches

Body Diameter:

0.750 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.500 inches

Body Length:

1.656 inches

Overall Diameter:

0.750 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Locking bushing

Features Provided:

Shaft locking device

Electrical Resistance Per Section:

250.0 ohms single section

NSN 5905-00-195-9451

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

3600.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0