## NSN 5905-00-196-4643

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-196-4643

22.500 kilohms  Resistance Tolerance In Percent: -0.100/+0.100	
Electrical Resistance: 22.500 kilohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:	
22.500 kilohms  Resistance Tolerance In Percent: -0.100/+0.100	
-0.100/+0.100	
Ambient Tempurature In Deg Celsius At Full Rated Power:	
· · · · · · · · · · · · · · · · · · ·	
125.0	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:	
145.0	
Tempurature Range Of Tempurature Coefficient In Deg Celsius:	
-65.0/+145.0	
Inclosure Method:	
Encapsulated	
Terminal Type:	
Wire lead	
Reliability Indicator:	
Established	
Reliability Failure Rate Level In Percent:	
0.010	
Body Diameter:	
0.265 inches	
Body Length:	
0.310 inches	
Power Dissipation Rating In Watts:	
0.125 free air	
Style Designator:	
Axial terminal each end	
Test Data Document:	
06481-900611 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, et	c.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A001a0	