## NSN 5905-00-196-5636

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-196-5636

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -10.0/+10.0 Electrical Resistance: 2.050 kiloms Resistance Tolerance In Percent: -0.030/+0.030 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator:
2.050 kilohms  Resistance Tolerance In Percent: -0.030/+0.030  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 1.000 inches  Body Diameter: 0.141 inches  Body Length: 0.391 inches  Power Dissipation Rating In Watts: 0.100 free air
Resistance Tolerance In Percent: -0.030/+0.030 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.000 inches  Body Diameter:  0.141 inches  Body Length:  0.391 inches  Power Dissipation Rating In Watts:  0.100 free air
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.000 inches  Body Diameter:  0.141 inches  Body Length:  0.391 inches  Power Dissipation Rating In Watts:  0.100 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+125.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.000 inches  Body Diameter:  0.141 inches  Body Length:  0.391 inches  Power Dissipation Rating In Watts:  0.100 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 1.000 inches  Body Diameter: 0.141 inches  Body Length: 0.391 inches  Power Dissipation Rating In Watts: 0.100 free air
Wire lead  Reliability Indicator:  Not established  Terminal Length: 1.000 inches  Body Diameter: 0.141 inches  Body Length: 0.391 inches  Power Dissipation Rating In Watts: 0.100 free air
Reliability Indicator: Not established  Terminal Length: 1.000 inches  Body Diameter: 0.141 inches  Body Length: 0.391 inches  Power Dissipation Rating In Watts: 0.100 free air
Not established  Terminal Length:  1.000 inches  Body Diameter:  0.141 inches  Body Length:  0.391 inches  Power Dissipation Rating In Watts:  0.100 free air
Terminal Length:  1.000 inches  Body Diameter:  0.141 inches  Body Length:  0.391 inches  Power Dissipation Rating In Watts:  0.100 free air
1.000 inches  Body Diameter: 0.141 inches  Body Length: 0.391 inches  Power Dissipation Rating In Watts: 0.100 free air
Body Diameter:  0.141 inches  Body Length: 0.391 inches  Power Dissipation Rating In Watts:  0.100 free air
0.141 inches  Body Length: 0.391 inches  Power Dissipation Rating In Watts: 0.100 free air
Body Length:  0.391 inches  Power Dissipation Rating In Watts:  0.100 free air
0.391 inches  Power Dissipation Rating In Watts:  0.100 free air
Power Dissipation Rating In Watts: 0.100 free air
0.100 free air
Style Designator:
Axial terminal each end
Test Data Document:
06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A001a0