Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-197-4679

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.030 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

3.250 inches

#### Mounting Bushing Length:

0.390 inches

#### Body Length:

#### 0.660 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

320.0

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.546 inches

#### Fragility Factor:

Moderately rugged

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unc

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

250.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

320.0



# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Insulated shaft **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0