

View Online at <https://aerobasegroup.com/nsn/5905-00-197-5152>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.74900 inches and 1.75000 inches

Pilot Length:

0.06200 inches

Overall Length:

1.645 inches

Undercut Diameter:

1.875 inches

Undercut Width:

0.07300 inches

Body Diameter:

2.000 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

0.625 inches

Body Length:

1.020 inches

Overall Diameter:

2.000 inches

Mounting Lip Diameter:

2.00000 inches

Mounting Lip Depth:

0.09300 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

1.50 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft Runout:

0.001 inches

Lateral Runout:

0.005 inches

Pilot Diameter Runout:

0.00150 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

1.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-200.0/+200.0 single section

Power Dissipation Rating Per Section In Watts:

10.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0