## NSN 5905-00-197-7011

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-197-7011

Electrical Resistance: 4.990 kilohms Resistance Tolerance in Percent: 4.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 4.55.0/+165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 4.55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Bedy Diameter: Between 0.120 inches and 0.140 inches Bedy Diameter: Between 0.120 inches and 0.421 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 4,990 kilohms Resistance Tolerance In Percent: 4,990 kilohms Resistance Tolerance In Percent: 4,990 kilohms Ambient Tempurature In Deg Celsius At Full Rated Power: 770.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1,375 inches and 1,625 inches Bedy Diameter: Between 0,120 inches and 0,140 inches Bedy Length: Between 0,391 inches and 0,421 inches Power Dissipation Rating In Watts: 0,250 free air Style Designator: Axial terminal each end Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.391 inches and 0.421 inches Body Length: Between 0.391 inches and 0.421 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Terminal Length: Between 1.375 inches and 1.625 inches Bedy Diameter: Between 0.120 inches and 0.140 inches Bedween 0.120 inches and 0.421 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 195750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 195750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 195750-100000 drawing, this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 195750-100000 drawing, this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 195750-100000 drawing, this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 195750-100000 drawing, this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 195750-100000 drawing, this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 195750-100000 drawing, this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 195750-100000 drawing, this is the date of the document that may be referenced in a basic governing drawing)	4.990 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Terminal Length: Between 1.375 inches and 1.625 inches Between 1.375 inches and 1.625 inches Between 0.120 inches and 0.140 inches Bedy Diameter: Between 0.120 inches and 0.421 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; escludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  165.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+165.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.120 inches and 0.140 inches  Body Length:  Between 0.120 inches and 0.421 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Avail terminal each end  Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  165.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+165.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.120 inches and 0.140 inches  Body Length:  Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.120 inches and 0.140 inches Body Diameter: Between 0.120 inches and 0.421 inches Body Length: Between 0.391 inches and 0.421 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.120 inches and 0.140 inches Body Length: Between 0.391 inches and 0.421 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Terst Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.120 inches and 0.140 inches Body Diameter: Between 0.391 inches and 0.421 inches Body Length: Between 0.391 inches and 0.421 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	165.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Bedy Diameter: Between 0.120 inches and 0.140 inches Bedy Length: Between 0.391 inches and 0.421 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.120 inches and 0.140 inches  Body Length:  Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	-55.0/+165.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.120 inches and 0.140 inches Body Length: Between 0.391 inches and 0.421 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.120 inches and 0.140 inches  Body Length:  Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Encapsulated
Reliability Indicator:  Not established  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.120 inches and 0.140 inches  Body Length: Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator:  Axial terminal each end  Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Terminal Type:
Note established  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.120 inches and 0.140 inches  Body Length: Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator:  Axial terminal each end  Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Wire lead
Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.120 inches and 0.140 inches  Body Length: Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator:  Axial terminal each end  Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Reliability Indicator:
Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.120 inches and 0.140 inches  Body Length:  Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Not established
Between 0.120 inches and 0.140 inches  Body Length:  Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Terminal Length:
Between 0.120 inches and 0.140 inches  Body Length:  Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Between 1.375 inches and 1.625 inches
Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Axial terminal each end  Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:	Body Diameter:
Between 0.391 inches and 0.421 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator:  Axial terminal each end  Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Between 0.120 inches and 0.140 inches
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Body Length:
0.250 free air  Style Designator:  Axial terminal each end  Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Between 0.391 inches and 0.421 inches
Style Designator:  Axial terminal each end  Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	0.250 free air
Test Data Document:  95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Style Designator:
95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:	Test Data Document:
Shelf Life: N/a Unit Of Measure:	95750-100000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: 	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure:	Shelf Life:
- <del>-</del>	N/a
 Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0