

View Online at <https://aerobasegroup.com/nsn/5905-00-198-4441>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

Between 1.249 inches and 1.374 inches

**Terminal Length:**

Between 0.140 inches and 0.172 inches

**Body Diameter:**

Between 0.844 inches and 0.906 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

Between 0.593 inches and 0.656 inches

**Mounting Bushing Length:**

Between 0.218 inches and 0.281 inches

**Body Length:**

Between 0.656 inches and 0.718 inches

**Overall Diameter:**

Between 0.984 inches and 1.078 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

1.00 inch-ounces

**Maximum Stop Torque:**

6.00 inch-ounces

**Nonturn Device Location:**

At 6 oclock

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear-bottom

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

8.000 ohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 295.0 and 305.0

**Power Dissipation Rating Per Section In Watts:**

12.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Stops

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A002a0