NSN 5905-00-198-9427

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-198-9427

Section Quantity:
2
Reliability Indicator:
Not established
Body Diameter:
1.062 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.188 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.000 kilohms 2nd section
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 1st section
Standard Taper Curve Per Section:
A 1st section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

N/a

NSN 5905-00-198-9427

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0