NSN 5905-00-199-0144

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-199-0144 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.969 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.969 inches **Shaft Style:** Round **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.500 inches **Fragility Factor:** Rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

Electrical Resistance Per Section:

100.0 ohms single section

Power Dissipation Rating Per Section In Watts:

25.0 free air single section

NSN 5905-00-199-0144

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



5	esistance	Tolerance	Per Section	In Percent:
۲	esistance	i olei ance	rei Section	ın Fercent.

-10.0 to 10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0