## NSN 5905-00-199-0152

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-199-0152 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.063 inches **Terminal Length:** 0.344 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.188 inches **Overall Diameter:** 1.406 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

50.000 kilohms 2nd section

## NSN 5905-00-199-0152

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
2.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 1st section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0