Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-199-0169

### Section Quantity:

2

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

1.062 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.000 inches

#### Mounting Bushing Length:

0.500 inches

#### Body Length:

## 0.562 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

### Nonturn Device Location:

At 3 oclock and at 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Locking bushing

## **Electrical Resistance Per Section:**

500.0 kilohms all sections

# Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 all sections

# Standard Taper Curve Per Section:

A all sections



## Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0