Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-199-6831

# Section Quantity:

1

Body Style:

Cylindrical

### **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.950 inches

#### **Body Length:**

0.600 inches

#### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

270.0

#### **Terminal Location:**

Lower adjacent side single row

### **Mounting Method:**

Terminal

### **Electrical Resistance Per Section:**

1.0 kilohms single section

### Rotary Actuator Travel In Angular Deg:

270.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

+0.0 to 200.0 single section

### Power Dissipation Rating Per Section In Watts:

0.5 free air single section

### **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

### Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

## Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

### Unit Of Measure:

--



Demilitarization:

No

Fiig:

A002a0