

View Online at <https://aerobasegroup.com/nsn/5905-00-200-9515>

Section Quantity:

1

Body Style:

Rectangular w/bushing/hole mounting

Reliability Indicator:

Not established

Body Diameter:

0.500 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.220 inches

Body Width:

0.320 inches

Body Height:

0.320 inches

Actuator Type:

Flush drive with slot-hole

End Application:

General purpose electronic test equipment gpete; missile, air-to-air, phoenix (aim-54)

Screw Thread Diameter:

0.190 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

20.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

7200.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Criticality Code Justification:

Feat

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0