NSN 5905-00-200-9668

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-200-9668 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.641 inches **Body Diameter:** 1.625 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 0.625 inches **Overall Diameter:** 1.718 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 312.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Maximum Stop Torque:** 192.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches Mechanical Backlash In Deg Angular Rotation: 1.5 **Screw Thread Diameter:** 0.375 inches

Screw Thread Series Designator: Unef

NSN 5905-00-200-9668

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Shaft seal
Electrical Resistance Per Section:
100.0 ohms single section
Rotary Actuator Travel In Angular Deg:
312.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0 to 4.5 -55 degrees celsius single section and +0.0 to 2.5 -25 degrees celsius single section and +0.0 to 1.5 0 degrees celsius single
section and -0.0 to 0.0 25 degrees celsius single section and -1.5 to 1.5 85 degrees celsius single section and +0.0 to 3.5 120 degrees
celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0