Nonprecision Wire Wound Variable Resistor - Page 1 of 2



201-2920

Nonprecision wire wound variable Resiste
View Online at https://aerobasegroup.com/nsn/5905-00-2
Section Quantity:
1
First Flat Length:
0.344 inches
Flat Height:
0.219 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Shaft Style:
Round, flatted
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock or at 6 oclock or at 9 oclock or at 12 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
22.000 ohms single section
Power Dissipation Rating Per Section In Watts:
50.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

---

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0