NSN 5905-00-201-2928

Section Quantity:

Reliability Indicator:

Not established First Flat Length:

0.438 inchesFlat Height:0.216 inches

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-201-2928

Shaft Diameter:
0.250 inches
Shaft Length:
1.000 inches
Mounting Bushing Length:
0.375 inches
Overall Diameter:
2.750 inches
Shaft Style:
Round, flatted
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
8.000 ohms single section
Resistance Tolerance Per Section In Percent:
-5.0 to 15.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
2 connector, receptacle

NSN 5905-00-201-2928

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Damilitarination.

Demilitarization:

No

Fiig:

A002a0