NSN 5905-00-201-3076

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-201-3076 **Section Quantity:** 1 **Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.875 inches **Shaft Length:** 1.000 inches **Body Length:** 1.438 inches **Mounting Hole/stud Circle Diameter:** 1.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Fragility Factor:** Rugged **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded hole **Features Provided:** Humidity proof **Electrical Resistance Per Section:**

Rotary Actuator Travel In Angular Deg:

20.0 kilohms single section

320.0

NSN 5905-00-201-3076

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 100.0 single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 turret Shelf Life: N/a **Unit Of Measure: Demilitarization:** No