Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-201-7078

### Section Quantity:

1

Body Style:

Cylindrical

### Reliability Indicator:

Not established

#### **Terminal Length:**

0.562 inches

#### **Body Diameter:**

0.500 inches

**Body Length:** 

0.328 inches

Actuator Type:

#### Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

295.0

### Maximum Starting Torque:

4.00 inch-ounces

#### Maximum Running Torque:

4.00 inch-ounces

#### Center To Center Distance Between Terminals:

0.200 inches

### **Terminal Location:**

Rear end

#### Mounting Method:

Terminal

#### **Electrical Resistance Per Section:**

5.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

295.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# Power Dissipation Rating Per Section In Watts:

0.375 free air single section

# **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

# Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section



Standard Taper Curve Per Section:

A single section

### Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0