NSN 5905-00-202-0180

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-202-0180 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Overall Length:** 1.000 inches **Body Diameter:** 2.093 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Body Length:** 1.000 inches **Overall Diameter:** 2.093 inches **Mounting Hole/stud Circle Diameter:** 1.250 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 351.0 **Maximum Starting Torque:** 203.00 inch-ounces **Maximum Running Torque:** 203.00 inch-ounces **Screw Thread Diameter:** 0.164 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:** 3 **Terminal Location:**

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

NSN 5905-00-202-0180

Precision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:	
Nonmetallic shaft	
Electrical Resistance Per Section:	
85.000 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
-0.50/+0.50 single section	
Power Dissipation Rating Per Section In Watts:	
2.5 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Function Characteristic Per Section:	
Single section linear	
Special Features:	
Mtg holes countersunk 5/32 in. Spaced 120 degrees apart on 1.250 in. Diameter circle	
Terminal Type And Quantity:	
3 solder stud	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A002a0	