NSN 5905-00-203-0005

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-203-0005 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.547 inches **Terminal Length:** 0.175 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.250 inches **Body Length:** 0.547 inches **Overall Diameter:** 1.100 inches **Shaft Bearing Type:** Sleeve **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 295.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.20 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.249 inches

Shaft End Play: 0.005 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.005 inches **Pilot Diameter Runout:**

0.0025 inches

Shaft Radial Play:

0.003 inches

NSN 5905-00-203-0005 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Terminal
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
600.0/+600.0 single section
Power Dissipation Rating Per Section In Watts:
0.333 free air single section
Resistance Tolerance Per Section In Percent:
20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4002a0