## NSN 5905-00-204-6940

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-204-6940

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.652 inches
Shaft Diameter:
Between 0.248 inches and 0.250 inches
Shaft Length:
Between 1.094 inches and 1.156 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.0 megohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:

A single section

-30.0 to 30.0 single section

**Standard Taper Curve Per Section:** 

## NSN 5905-00-204-6940

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Special Features:
One 7 in. Is with terminal and marker soldered to each lug
Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0