Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-204-6940

View	Online at https://aerobasegroup.com/nsn/5905-00-204-0
Secti	on Quantity:
1	
Body	Style:
Cyline	drical bushing mounted
Relia	bility Indicator:
Not e	stablished
Body	Diameter:
0.652	inches
Shaft	Diameter:
Betwe	een 0.248 inches and 0.250 inches
Shaft	Length:
Betwe	een 1.094 inches and 1.156 inches
Mour	ting Bushing Length:
0.250	inches
Body	Length:
0.500	inches
Shaft	Style:
Roun	d, slotted
Actua	ator Type:
Single	e shaft
Nont	urn Device Location:
At 9 c	oclock
Nont	urn Device Radius:
0.531	inches
Screv	w Thread Diameter:
0.375	inches
Screv	w Thread Series Designator:
Unef	
Screv	w Thready Qty Per Inch (tpi):
32.0	
Term	inal Location:
Radia	Ily positioned over less than half the circumference
Mour	ting Method:
Stand	lard bushing
	rical Resistance Per Section:
25.0 ı	negohms single section
	r Dissipation Rating Per Section In Watts:
	ee air single section
	stance Tolerance Per Section In Percent:
-30.0	to 30.0 single section
	dard Taper Curve Per Section:
	ale section

A single section



Special Features:

One 7 in. Is with terminal and marker soldered to each lug

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0