Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-204-6947

#### Section Quantity:

2

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### First Flat Length:

0.438 inches

#### Flat Height:

0.216 inches

Body Diameter:

1.125 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

#### 2.500 inches

#### Mounting Bushing Length:

0.250 inches

#### **Body Length:**

0.969 inches

#### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

600.000 ohms 2nd section

## Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

# NSN 5905-00-204-6947 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 2nd section

Standard Taper Curve Per Section:

C 1st section

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0