## NSN 5905-00-204-6950

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-204-6950 **Section Quantity: Overall Height:** 1.328 inches **Overall Width:** 1.125 inches **Shaft Diameter:** Between 0.188 inches and 0.265 inches **Shaft Length:** Between 0.688 inches and 1.000 inches **Mounting Bushing Length:** 0.375 inches **Shaft Style:** Round **Actuator Type:** Dual concentric **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 400.000 kilohms 1st section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 2nd section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

Unit Of Measure:
-Demilitarization:

## NSN 5905-00-204-6950

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0