NSN 5905-00-204-6963

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-204-6963 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.650 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:
Unef

Screw Thready Qty Per Inch (tpi):
32.0

Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing

Electrical Resistance Per Section:
500.0 kilohms all sections

Power Dissipation Rating Per Section In Watts:
2.0 free air all sections

Resistance Tolerance Per Section In Percent:

Standard Taper Curve Per Section:

A all sections

-10.0 to 10.0 all sections

NSN 5905-00-204-6963

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0