NSN 5905-00-204-6972

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-204-6972

Section Overtitus
Section Quantity:
1 Radio Studen
Body Style:
Rectangular
Reliability Indicator:
Not established
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Body Length:
1.000 inches
Body Width:
2.000 inches
Body Height:
2.125 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.234 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing w/shaft seal
Electrical Resistance Per Section:
500.0 ohms single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:

Standard Taper Curve Per Section: A single section

-5.0 to 5.0 single section

NSN 5905-00-204-6972

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0