## NSN 5905-00-204-7747

Film Fixed Resistor - Page 1 of 1

Mil-std (military Standard):

Mil-prf-55182 spec.



View Online at https://aerobasegroup.com/nsn/5905-00-204-7747

Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
175.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Mil-std-1276 Wire Lead Type Designator:
C
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
1.500 inches
Body Diameter:
Between 0.085 inches and 0.165 inches
Body Length:
Between 0.260 inches and 0.437 inches
Power Dissipation Rating In Watts:
0.125 free air
Special Features:
Electrical resistance 1.000 megohms; resistance tolerance in percent m1.000/p1.000; temp coefficient of resistance in ppm per degrees
celsius m50.0/p50.0; temp range of temp coefficient in degrees celsius m55.0/175.0
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-55182/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0