NSN 5905-00-204-8175

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-204-8175 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear-bottom **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 1.000 megohms single section **Power Dissipation Rating Per Section In Watts:** 0.1 free air single section **Switch Current Type And Rating In Amps:** 3.000 ac **Terminal Type And Quantity:**

5 tab, solder lug

Shelf Life:

N/a

NSN 5905-00-204-8175

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0