## NSN 5905-00-208-3798

Precision Wire Wound Variable Resistor - Page 1 of 3

View Online at https://aerobasegroup.com/nsn/5905-00-208-3798



**Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 3.633 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.414 inches **Body Length:** 3.187 inches **Overall Diameter:** 0.875 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round Switch Type: Rotary Switch Voltage Rating In Volts: 28.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3130.0 **Maximum Starting Torque:** 1.30 inch-ounces

## NSN 5905-00-208-3798

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Switch Operating Position:
440 degrees rotation from cw and ccw end
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Switch
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-2.00/+2.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Function Conformity Per Section:
Single section absolute linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section table
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section

1.500 dc

**Switch Current Type And Rating In Amps:** 

## NSN 5905-00-208-3798

Precision Wire Wound Variable Resistor - Page 3 of 3



## **Test Data Document:**

00724-10-00253-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:
-----------------------------

8 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0