NSN 5905-00-209-0318

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-209-0318 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.320 inches **Overall Height:** 0.320 inches **Overall Width:** 0.190 inches **Mounting Hole Diameter:** 0.088 inches **Shaft Diameter:** 0.110 inches **Shaft Length:** 0.250 inches **Body Length:** 1.250 inches **Body Width:** 0.190 inches **Body Height:** 0.320 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7920.0 **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 0.10 inch-ounces **Lateral Distance Between Mounting Hole Centers:**

1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

NSN 5905-00-209-0318

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:	
100.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
7920.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
175.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-70.0 to 70.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Resistance Tolerance Per Section In Percent:	
-5.0 to 5.0 single section	
Actuator Travel Control Feature:	
Clutch	
Criticality Code Justification:	
Feat	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Special Features:	
Item must comply with requirements of defense electronics supply center production standard no. L01102	
Terminal Type And Quantity:	
3 wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	