## NSN 5905-00-209-4475

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-209-4475

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
liilength:
2.125 inches
Terminal Length:
0.297 inches
Body Diameter:
1.156 inches
Shaft Diameter:
Between 0.248 inches and 0.250 inches
Shaft Length:
1.500 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
liidiameter:
1.453 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.578 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:

25.000 kilohms single section

## NSN 5905-00-209-4475

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance	<b>Tolerance</b>	Per	Section	In	Percent:

-10.0 to 10.0 single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0