NSN 5905-00-210-4269

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-210-4269

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Pilot Diameter:
1.87500 inches
Pilot Length:
0.06200 inches
Overall Length:
3.625 inches
Body Diameter:
1.820 inches
Shaft Length:
1.564 inches
Body Length:
1.938 inches
Overall Diameter:
2.000 inches
Mounting Lip Diameter:
2.00000 inches
Mounting Lip Depth:
0.06200 inches
Shaft Style:
Round, undercut
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 3600.0 and 3610.0
Undercut Length:
0.125 inches
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
40.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3610.0
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section

·30.0/+30.0 single section

NSN 5905-00-210-4269

Precision Wire Wound Variable Resistor - Page 2 of 2



Special Features:
Rd shaft w/2undercuts, 2 dia. And integral gear
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0