NSN 5905-00-211-1061

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-211-1061

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.375 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.250 inches
Body Length:
2.750 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Hermetically sealed
Electrical Resistance Per Section:
30.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125 0 single section

125.0 single section

A002a0

NSN 5905-00-211-1061 Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
25.0 to 25.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
2.0 to 2.0 single section
Actuator Travel Control Feature:
Continuous motion
Criticality Code Justification:
Zzzy
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Reference Number Differentiating Characteristics:
Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig: